



Photo et textes non contractuels

Product Information:

Fully-hydraulic semi automatic cycle of band, arch and arch
 Very highly rigid steel cast iron arch
 3-point lubrication system through electropump
 Detachable vice support
 Band tension microswitch through rotation detection
 Adjustable band tension through automatic stop safety system in case the band breaks or slips
 Adjustable band guides fitted with carbide tips and bearings
 Easy rotation of arch with bearings (45° to the right and 60° to the left)
 Feed and cutting pressure adjustment system
 24V very low voltage controls
 Motor protection through thermal circuit breaker
 Electrical protection IP54
 Locking main switch
 Emergency Stop through mushroom stay put button
 Band cover fitted with a positive microswitch
 Hydraulic vice
 Bac liquide de refroidissement de 40 litres de contenance
 Hot weather adaptation on request
 Can be modified to 230V three-phase on request
 * with thickness

SR 550 BSA VA

(Ref. 20114148)

Usage très intensif

Guarantee:  CE

Technical characteristics:

Height (cm) : 208.00
 Width (cm) : 118.00
 Length (cm) : 205.00
 Net weight (Kg) :
 Power(kW)
 Power (V) 3-phase 400V
 Speed (m/min)
 Round cutting capacity (mm) at 90°
 Square cutting capacity (mm) at 90°
 Rectangle cutting capacity (mm) at 90°
 Left round cutting capacity (mm) at 45°
 Left square cutting capacity (mm) at 45°
 Left rectangle cutting capacity (mm) at 45°
 Left round cutting capacity (mm) at 60°
 Left square cutting capacity (mm) at 60°
 Left rectangle cutting capacity (mm) at 60°
 Vice opening (mm)
 Working height (mm)
 Tape (mm)
 Right rectangle cutting capacity (mm) at 45°
 Right round cutting capacity (mm) at 45°
 Left square cutting capacity (mm) at 45°

Supplied with stand, band and cutting stop 600 mm