



ULTRA 200 TMBT

(Ref. 20113137)

Dry grinding and band polishing of ferrous metals
Usage très intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

- Cast aluminium body
- Fitted with self-lubricated oiltight bearings
- Control box complying with high school and administration requirements
- 4-point locking Start/Stop switch
- Lack of voltage-coil safety device
- Emergency Stop with mushroom stay put button
- Polycarbonate protective shield
- Motor internal automatic heat protection
- Pressed metal sheet carters fitted with a nozzle to collect dust - diameter 30 mm
- Pressed metal sheet band carters fitted with a nozzle to collect dust - diameter 100 mm
- 0° to 90° orientable band carter to work horizontally or vertically
- Adjustable anti-spark shield and tool-holders 2 mm away from the wheel
- Hot weather adaptation on request
- 3-phase 230V version of the bench grinder on request

Supplied with:

- Grinding Wheel A 60 M
- Belt GR80

Technical characteristics:

- Height (cm) : 63.00
- Width (cm) : 27.00
- Length (cm) : 62.00
- Net weight (Kg) : 37.00
- Power(kW)
- Power (V) 3-phase 400V
- Rotation speed 1 (rpm)
- Endless band dimension (mm)
- Wheel-1 dimension (mm)
- Wheel-1 grain
- Band grain
- Diameter (mm)