



SR 285 DG SAV

(Ref. 20114128)

Dry steel, stainless steel and aluminium sawing with coolant with coolant

Usage intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

Fully-hydraulic semi automatic cycle of band, arch and arch
Electronic speed variator
Semi automatic down move of the arch
Very highly rigid steel cast iron arch
Band guides fitted with bearings and carbide tips ensuring a good wear resistance to band
Adjustable front mobile band guide
2-point lubrication system through electropump
Vice support tilting with the arch
Hydraulic vice
24V very low voltage controls
Emergency Stop through mushroom stay put button
Band cover fitted with a microswitch
Motor protection through thermal circuit breaker
Electrical protection IP54
Coaxial reducer motor

Supplied with:

- base
- band saw
- adjustable cut stop

Technical characteristics:

Height (cm) : 105.40
Width (cm) : 75.00
Length (cm) : 167.60
Net weight (Kg) : 310.00
Power(kW) 1,1
Power (V) 3-phase 400V
Speed (m/min)
Round cutting capacity (mm) at 90°
Square cutting capacity (mm) at 90°
Rectangle cutting capacity (mm) at 90° 200 x 285
Left round cutting capacity (mm) at 45°
Left square cutting capacity (mm) at 45°
Left rectangle cutting capacity (mm) at 45° 140 x 180
Left round cutting capacity (mm) at 60°
Left square cutting capacity (mm) at 60°
Left rectangle cutting capacity (mm) at 60° 95 x 110
Vice opening (mm) 375
Working height (mm)
Tape (mm)
Right rectangle cutting capacity (mm) at 45° 90 x 150
Right round cutting capacity (mm) at 45°
Left square cutting capacity (mm) at 45°