



## JET 15 i

(Ref. 20402040)

Water and dust suction

**Usage très intensif**

Norm: EN 60335-2-69

Guarantee:  

**Photo et textes non contractuels**

### Product Information:

Manual unclogging system of the filter using a single button  
 Water-resistant high-efficiency 9.9% Class M cartridge filter  
 Metal accessories and stainless steel tubes  
 Carbon-fibre reinforced base  
 Storage unit of accessories integrated to the base  
 Large 2-wheel + 2 castors for a stabilised stability  
 Anti-crushing shielded hose  
 By-pass cooling down system 1450W motor designed for continuous heavy-duty jobs (air is sucked by a third turbine on top of the motor, only for cooling down)  
 Suction, depression and cutting-off high-performance  
 Anti-static electricity plate connected to earth  
 Neoprene power table HO7 RNF length 7 m

### Technical characteristics:

Height (cm) : 60.00  
 Width (cm) : 42.50  
 Length (cm) : 46.00  
 Net weight (Kg) : 13.18  
 Repairability index  
 Power (W)  
 Power (V) 1-phase 230V  
 Tank stainless steel  
 Tank capacity (l)  
 Depression (Kpa) 26.7  
 Flow (l/min) 4 200  
 Sound level (dBA)  
 Atex Zone 22 No  
 Accessory diameter (mm)  
 Unclogging Yes  
 Class-M approved No  
 Vacuum cleaner filter Class M PET cartridge  
 Synchro socket No  
 Cable length (m)  
 Tank capacity (L)

### Standard accessories:

- Bent tubes 2 x 500 mm Ø 32 mm
- hose Ø 32 mm, length 2,2 m
- liquid nozzle de 400 mm
- dual-purpose nozzle - 270 mm
- round brush
- flat nozzle
- Padding nozzle
- Class M cartridge filter PTFE