



30 CV

(Ref. 20502022)

Drilling and tapping of metals, plastic materials and wood, with coolant

Usage intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

- Steel cast iron frame, head and stand
- Steel column
- Spindle fitted on bearings
- 24V very low voltage controls
- Emergency Stop through mushroom stay put button
- Locking main switch 4 points
- Semi automatic tapping system + instant return
- Servo detachable chuck protective shield
- Large table mécanicien, Rack-driven table
- Electronic speed variator
- Digital display of the spindle speed
- LED lighting 24 V

Supplied with:

- Tap-holder chuck M3 to M16
- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift
- BSH 7 vice and set of clamps

Technical characteristics:

- Height (cm) : 176.50
- Width (cm) : 52.50
- Length (cm) : 66.00
- Net weight (Kg) : 220.00
- Power(kW)
- Power (V) 3-phase 400V
- Spindle speed (rpm)
- Max. drilling capacity (mm)
- Max. tapping capacity (mm)
- Morse taper MT3
- Column dia (mm)
- Spindle stroke (mm)
- Number of gears
- d: spindle/column distance (mm)
- e: spindle/base distance (mm) 1 150
- f: spindle/table distance (mm)
- Table dimension (mm)
- Distance between table grooves (mm)
- Lighting Yes
- Servo screen Yes
- Reversible vice table No
- Coolant Yes
- Automatic down motion (mm/tr) No
- Slow down motion No
- Semi automatic tapping Yes
- Cross motion table No