PRODUCT SHEET | Update File: 11/13/2026

DIAMOND CORE DRILL | Dry diamond ring



D 32

(Ref. 11101516)

Dry drilling of hollow building materials, breeze blocks, bricks, aerated concrete
Usage intensif

Photo et textes non contractuels

Product Information:

Laser-welded segment ring
Spline segments to better cool down and discharge dust
Designed for dry core-drilling on portable drilling machine or rotary hammer
Using only the drill to hammer drill a center hole
No-hammer core-drilling using the ring + center drill
Assembly with hexagonal rod or SDS PLUS
Building construction materials: non-reinforced concrete, brick, cellular concrete
Convenient core-drilling and finishing speed in building construction materials

Technical characteristics:

Height (cm) : 19.00
Width (cm) : 3.20
Length (cm) : 3.20
Net weight (Kg) : 0.28
For machine Drilling Portable machine
Diameter (mm)
Ring length (mm)
Useful length (mm)
Fitting model
Ring height (mm)
Ring thickness (mm)
Number of rings

SIDAMO - ZI des Gailletrous - 41260 La Chaussée St Victor
Tél : +33 (0)2 54 90 28 28 - Fax : 08 97 65 65 10 - Mail : sidamo@sidamo.com - Service utilisateur / Tél : 02 54 74 02 16