

25 F HSS 118°

(Ref. 11500002)

Drilling of low-alloy steels, ferrous metals, aluminium and cast iron
Usage intensif

Photo et textes non contractuels

Product Information:

Box of 25 HSS metal drills
Split-point grinding:reduction of the drill tip. Enables the easy self-centring of the drill bit on the smoothest of surfaces. Significantly reduces the requ ried axial load.
118° tip: 118° tip angle for the sharpening of the drill bit. Suitable for gen eral uses in long chip materials. Allows a quick attack of the material and easy centering.
Cylindrical shank: the diameter of the shank is equal to the diameter of th e tip. Enables versatile use on portable electrical tools and machine tools.
30° type N flute: normal flute profile with a 30° helix angle. Suitable for ge neral use.
Cut-ground drill, more resistance and excellent drilling accuracy.
Provides good rigidity to the tool, as well as excellent drilling precision.
High-speed steel: HSS substrate. For general uses in steel up to 950 N/mm ², cast iron and aluminium.

Technical characteristics:

Height (cm) : 6.00
Width (cm) : 11.50
Length (cm) : 20.00
Net weight (Kg) : 1.10
For machine Floor machine drill, portable drill
Characteristic 1 Box of drill bits HSS
Diameter (mm)
Shank (mm) Cylindrical