



## ULTRA 150 TMT FR

(Ref. 20113134)

Dry grinding of ferrous metals  
**Usage très intensif**

Guarantee:  

Photo et textes non contractuels

### Product Information:

Cast aluminium body  
Fitted with self-lubricated oiltight bearings  
Electrical brake powered by an Emergency Stop, stop in less than 5 seconds  
Control box complying with high school and administration requirements  
24V very low voltage controls  
Start/Stop switch  
Switching on lamp  
3-point locking circuit breaker  
Lack of voltage-coil safety device  
Polycarbonate protective shield  
Motor internal automatic heat protection  
Pressed metal sheet carters fitted with a nozzle to collect dust  
Adjustable anti-spark shield and tool-holders 2 mm away from the wheel  
Hot weather adaptation on request  
3-phase 230V version of the bench grinder on request

### Supplied with:

- Grinding Wheel A 24 R
- Grinding Wheel A 60 M

### Technical characteristics:

Height (cm) : 54.50  
Width (cm) : 25.00  
Length (cm) : 42.00  
Net weight (Kg) : 25.00  
Power(kW)  
Power (V) 3-phase 400V  
Rotation speed 1 (rpm)  
Wheel-1 dimension (mm)  
Wheel-2 dimension (mm)  
Wheel-1 grain  
Wheel-2 grain  
Diameter (mm)