

SR 320 BSA

(Ref. 20114017)

Dry steel sawing with coolant
Usage très intensif

Guarantee: 3 ans

Photo et textes non contractuels

Product Information:

Fully-hydraulic semi automatic cycle of band, arch and arch
Very highly rigid cast aluminium arch
3-point lubrication system through electropump
Detachable vice support
Band tension microswitch through rotation detection
Adjustable band tension through automatic stop safety system in case the band breaks or slips
Adjustable band guides fitted with carbide tips and bearings
Easy rotation of arch with bearings (45ø to the right and 60ø to the left)
Feed and cutting pressure adustment system
24V very low voltage controls
Motor protection through thermal circuit breaker
Electrical protection IP54
Locking main switch
Emergency Stop through mushroom stay put button
Band cover fitted with a positive microswitch
Hydraulic vice
Bac liquide de refroidissement de 40 litres de contenance
Hot weather adaptation on request
Can be modified to 230V three-phase on request

Supplied with stand, band and cutting stop 600 mm

Technical characteristics:

Height (cm) : 132.00
Width (cm) : 150.00
Length (cm) : 96.00
Net weight (Kg) : 620.00
Power(kW)
Power (V) 3-phase 400V
Speed (m/min)
Round cutting capacity (mm) at 90
Squre cutting capacity (mm) at 90°
Rectangle cutting capacity (mm) at 90°
Left round cutting capacity (mm) at 45°
Left square cutting capacity (mm) at 45°