

TS 250

(Ref. 20114087)

Cutting-off of metal profiles with coolant
Usage régulier

Guarantee: 3

Photo et textes non contractuels

Product Information:

"45ø tilting head to the left and the right
Rapid clamping vice.
Burr-free double vice
Mobile jaw to perform right 45° cut
Protective cover of detachable saw mill
Lubrication system of saw mill using a pump
Drive through an oil-bath reducer
Steel cast iron frame
Control arm fitted with a trigger switch
Very low voltage controls 24 V
Emergency Stop through a mushroom stay put buTon
Gear switch
Electrical insulation IP 54

Technical characteristics:

Height (cm) : 157.30
Width (cm) : 96.00
Length (cm) : 93.50
Net weight (Kg) : 130.00
Power(kW)
Power (V) 3-phase 400V
Rotation speed (rpm)
Round cutting capacity (mm) at 90
Squre cutting capacity (mm) at 90°
Rectangle cutting capacity (mm) at 90°
Left round cutting capacity (mm) at 45°
Left square cutting capacity (mm) at 45°
Left rectangle cutting capacity (mm) at 45°
Vice opening (mm)
Working height (mm)
Dimension of the blade
Right rectangle cutting capacity (mm) at 45°
Right round cutting capacity (mm) at 45°
Left square cutting capacity (mm) at 45°
Abrasive disc dimension (mm) 3-phase 400V