

SR 170 MV

(Ref. 20114099)

Dry steel, stainless steel and aluminium sawing with coolant with coolant
Usage régulier

Guarantee: 3 ans

Photo et textes non contractuels

Product Information:

Cast aluminium arch
Tilting arch for left cuts up to 60°
Band guides fitted with bearings
Adjustable front mobile band guide
Arch return spring
Two-point lubrication system using an electro pump
Manual adjustment of band tension
Rapid clamping vice
Coaxial reducer motor
Electronic speed variator
Adjustable trigger switch handle
Emergency Stop with mushroom stay put buTon

Supplied with Stand, ruban, and butée de coupe

Technical characteristics:

Height (cm) : 160.00
Width (cm) : 100.00
Length (cm) : 51.00
Net weight (Kg) : 102.00
Power(kW)
Power (V) 1-phase 230V
Speed (m/min) 20 : 65
Round cutting capacity (mm) at 90
Squre cutting capacity (mm) at 90°
Rectangle cutting capacity (mm) at 90°
Left round cutting capacity (mm) at 45°
Left square cutting capacity (mm) at 45°
Left rectangle cutting capacity (mm) at 45°
Left round cutting capacity (mm) at 60°
Left square cutting capacity (mm) at 60°
Left rectangle cutting capacity (mm) at 60°
Vice opening (mm)
Working height (mm)
Tape (mm)