

SR 320 BSA VA

(Ref. 20114114)

Usage très intensif

Guarantee: 3 ans

Photo et textes non contractuels

Product Information:

Fully-hydraulic semi automatic cycle of band, arch and arch Digital readin g and adjustment of:
- Variable speed of the band
- Up move of the arch
- Number of cuts made

Very highly rigid cast aluminium arch 3-point lubrication system through e lectropump Detachable vice support Band tension microswitch through rot ation detection Adjustable band tension through automatic stop safety sys tem in case the band breaks or slips Adjustable band guides fitted with car bide tips and bearings Easy rotation of arch with bearings (45° to the right and 60° to the left) Feed and cutting pressure adustment system 24V ver y low voltage controls Motor protection through thermal circuit breaker El ectrical protection IP54 Locking main switch Emergency Stop through mus hroom stay put button Band cover fitted with a positive microswitch Hydra ulic vice Tank of cooling fluid (capacaity 40 litres) Hot meather adaptation on request Three-phase 230 V modification on request

Technical characteristics:

Height (cm) : 132.00
Width (cm) : 150.00
Length (cm) : 96.00
Net weight (Kg) : 620.00
Power(kW)
Power (V) 3-phase 400V
Speed (m/min) 20 : 100
Round cutting capacity (mm) at 90
Squre cutting capacity (mm) at 90°
Rectangle cutting capacity (mm) at 90°
Left round cutting capacity (mm) at 45°
Left square cutting capacity (mm) at 45°
Left rectangle cutting capacity (mm) at 45°
Left round cutting capacity (mm) at 60°
Left square cutting capacity (mm) at 60°
Left rectangle cutting capacity (mm) at 60°
Vice opening (mm)

Supplied with stand, band and cutting stop 600 mm

SIDAMO - ZI des Gailletrous - 41260 La Chaussée St Victor
Tél : +33 (0)2 54 90 28 28 - Fax : 08 97 65 65 10 - Mail : sidamo@sidamo.com - Service utilisateur / Tél : 02 54 74 02 16