



Photo et textes non contractuels

## SR 320 DG DAV

(Ref. 20114127)

Usage intensif

Guarantee:  

### Product Information:

Left and right cutting  
Electronic speed variator  
Autonomous down move of the arch  
Very highly rigid steel cast iron arch  
Band guides fitted with bearings and carbide tips ensuring a good wear resistance to band  
Adjustable front mobile band guide  
2-point lubrication system through electropump  
Vice support tilting with the arch  
Hydraulic vice  
24V very low voltage controls  
Emergency Stop through mushroom stay put button  
Band cover fitted with a microswitch  
Motor protection through thermal circuit breaker  
Electrical protection IP54  
Coaxial reducer motor

### Supplie with:

- base
- band saw
- adjustable cut stop

### Technical characteristics:

Height (cm) : 150.00  
Width (cm) : 80.00  
Length (cm) : 175.00  
Net weight (Kg) : 417.00  
Power(kW) 2,2  
Power (V) 3-phase 400V  
Speed (m/min)  
Round cutting capacity (mm) at 90°  
Square cutting capacity (mm) at 90°  
Rectangle cutting capacity (mm) at 90° 260 x 320  
Left round cutting capacity (mm) at 45°  
Left square cutting capacity (mm) at 45°  
Left rectangle cutting capacity (mm) at 45°  
Left round cutting capacity (mm) at 60°  
Left square cutting capacity (mm) at 60°  
Left rectangle cutting capacity (mm) at 60°  
Vice opening (mm) 270  
Working height (mm)  
Tape (mm)  
Right rectangle cutting capacity (mm) at 45° 220 x 150  
Right round cutting capacity (mm) at 45° 175  
Left square cutting capacity (mm) at 45° 200