

SR 350 DG SAV

(Ref. 20114129)

Dry steel, stainless steel and aluminium sawing with coolant with coolant
Usage intensif

Guarantee: 3 ans

Photo et textes non contractuels

Product Information:

Fully-hydraulic semi automatic cycle of band, arch and arch
Electronic speed variator
Semi automatic down move of the arch
Very highly rigid steel cast iron arch
Band guides fitted with bearings and carbide tips ensuring a good wear re sistance to band
Adjustable front mobile band guide
2-point lubrication system through electropump
Vice support tilting with the arch
Hydraulic vice
24V very low voltage controls
Emergency Stop through mushroom stay put button
Band cover fitted with a microswitch
Motor protection through thermal circuit breaker
Electrical protection IP54
Coaxial reducer motor

Supplied with:
- base
- saw blade
- adjustable cut stop

Technical characteristics:

Height (cm) : 166.00
Width (cm) : 75.00
Length (cm) : 195.00
Net weight (Kg) : 500.00
Power(kW) 1,5
Power (V) 3-phase 400V
Speed (m/min)
Round cutting capacity (mm) at 90
Squre cutting capacity (mm) at 90°
Rectangle cutting capacity (mm) at 90° 220 x 350
Left round cutting capacity (mm) at 45°
Left square cutting capacity (mm) at 45°
Left rectangle cutting capacity (mm) at 45° 170 x 230
Left round cutting capacity (mm) at 60°
Left square cutting capacity (mm) at 60°
Left rectangle cutting capacity (mm) at 60° 150 x 100
Vice opening (mm) 375
Working height (mm) 885
Tape (mm)
Right rectangle cutting capacity (mm) at 45° 140 x 200
Right round cutting capacity (mm) at 45°
Left square cutting capacity (mm) at 45°