



Photo et textes non contractuels

EXPERT 250 SR DGDA

(Ref. 20114136)

Dry steel sawing with coolant

Usage régulier

Guarantee:  **3** 

Product Information:

Cuts left and right
Aircast fram
Saw blade guides equipped with bearings and carbide pads to ensure excellent resistance to saw blade wear
Adjustable anterior tape guide
Autonomous descent by gravity controlled by hydraulic cylinder
2-point electro-pump lubrication device
Safety micro-switch and tension gauge saw blade
Fast-tightening set mounted on game catch-up slide
Control desk in front
Very low voltage controls 24 V
Stopping punch to hook
Carter saw equipped with a positive micro-reuptor
Motor protection by heat breaker
Motor with coaxial gearbox

Supplied with base, saw blade and 500 mm adjustable cut stop

Technical characteristics:

Height (cm) : 180.00
Width (cm) : 100.00
Length (cm) : 185.00
Net weight (Kg) : 306.00
Power(kW)
Power (V) 3-phase 400V
Speed (m/min)
Round cutting capacity (mm) at 90°
Square cutting capacity (mm) at 90°
Rectangle cutting capacity (mm) at 90°
Left round cutting capacity (mm) at 45°
Left square cutting capacity (mm) at 45°
Left rectangle cutting capacity (mm) at 45°
Left round cutting capacity (mm) at 60°
Left square cutting capacity (mm) at 60°
Left rectangle cutting capacity (mm) at 60°
Vice opening (mm)
Working height (mm)
Tape (mm)
Right rectangle cutting capacity (mm) at 45°
Right round cutting capacity (mm) at 45°
Left square cutting capacity (mm) at 45°