



Photo et textes non contractuels

JET 60

(Ref. 20402005)

Usage très intensif

Norm: EN 60335-2-69

Guarantee:  

Product Information:

"Fitted with a high-efficiency 99.9% Class M filter
Metal accessories and stainless steel tubes
Anti-crushing shielded hose
Tilting tank to easily empty liquids
Trolley fitted with 4 wheels for an optimised motion
Dual turbine suction
By-pass cooling down system motor designed for continuous heavy-duty jobs (air is sucked by a third turbine on top of the motor, only for cooling down)
Anti-static electricity plate connected to earth
Neoprene power cable HO7 RNF length 7 m

"Standard metal accessories:

- 2 user-friendly bent tubes ensuring a quiet use
 - 1 Dust nozzle - 400 mm
 - 1 liquid nozzle - 400 mm
 - 1 accessory support
- Standard plastic accessories:
- 1 round brush
 - 1 flat nozzle
 - 1 round brush fitting
 - 1 hose - 2500 mm

Technical characteristics:

Height (cm) : 90.00
Width (cm) : 56.00
Length (cm) : 60.00
Net weight (Kg) : 30.00
Power (W)
Power (V) 1-phase 230V
Tank stainless steel
Tank capacity (l)
Depression (Kpa) 23.52
Flow (l/min) 7 070
Sound level (dBA) 84.4
Atex Zone 22 No
Accessory diameter (mm)
Unclogging No
Class-M approved No
Vacuum cleaner filter Class M
Synchro socket No
Cable length (m)
Tank capacity (L)