



Photo et textes non contractuels

## JET 15 i

(Ref. 20402040)

Water and dust suction  
**Usage très intensif**

Norm: EN 60335-2-69

Guarantee:  

### Product Information:

Manual unclogging system of the filter using a single button  
Water-resistant high-efficiency 9.9% Class M cartridge filter  
Metal accessories and stainless steel tubes  
Carbon-fibre reinforced base  
Storage unit of accessories integrated to the base  
Large 2-wheel + 2 castors for a stabilised stability  
Anti-crushing shielded hose  
By-pass cooling down system 1450W motor designed for continuous heavy-duty jobs (air is sucked by a third turbine on top of the motor, only for cooling down)  
Suction, depression and cutting-off high-performance  
Anti-static electricity plate connected to earth  
Neoprene power table HO7 RNF length 7 m

### Standard accessories:

- Bent tubes 2 x 500 mm Ø 32 mm
- hose Ø 32 mm, length 2,2 m
- liquid nozzle de 400 mm
- dual-purpose nozzle - 270 mm
- round brush
- flat nozzle
- Padding nozzle
- Class M cartridge filter PTFE

### Technical characteristics:

Height (cm) : 60.00  
Width (cm) : 42.50  
Length (cm) : 46.00  
Net weight (Kg) : 13.18  
Repairability index  
Power (W)  
Power (V) 1-phase 230V  
Tank stainless steel  
Tank capacity (l)  
Depression (Kpa) 26.7  
Flow (l/min) 4 200  
Sound level (dBA)  
Atex Zone 22 No  
Accessory diameter (mm)  
Unclogging Yes  
Class-M approved No  
Vacuum cleaner filter Class M PET cartridge  
Synchro socket No  
Cable length (m)  
Tank capacity (L)