

steel tank



Photo et textes non contractuels

## JET 60 i DR

(Ref. 20402049)

Water, dust, soot and ash aspiration

**Usage très intensif**

Norm: EN 60335-2-69

Guarantee:  

### Product Information:

"Manual unclogging system of the filter using a single button  
special class M cartridge filter for fuel soot  
Anti-clogging nylon over filter  
Metal accessories and stainless steel tubes  
Storage unit of accessories integrated to the trolley  
Large reinforced 2-wheel + 2-castor trolley for an optimised stability  
Swivelling tank making easier liquid emptying  
Anti-crushing shielded hose  
Dual-turbine suction  
By-pass cooling down system motor designed for heavy-duty jobs (air is sucked by a third turbine on top of the motor, only for cooling down)  
Anti-static electricity plate connected to earth  
Separate switch per motor  
Neoprene power table HO7 RNF length 7 m"

#### "Standard accessories:

- Bent tubes 2 x 500 mm Ø 40 mm
- hose Ø 40 mm, length 5 m
- Dust nozzle - 400 mm
- flat nozzle inox 600 mm
- Class H cartridge filter PTFE

### Technical characteristics:

Height (cm) : 97.00  
Width (cm) : 62.00  
Length (cm) : 56.50  
Net weight (Kg) : 33.20  
Power (W)  
Power (V) 1-phase 230V  
Tank stainless steel  
Tank capacity (l)  
Depression (Kpa) 23.52  
Flow (l/min) 7 070  
Sound level (dBA) 76.5  
Atex Zone 22 No  
Accessory diameter (mm)  
Unclogging Yes  
Class-M approved No  
Vacuum cleaner filter Class H cartridge  
Synchro socket No  
Cable length (m)  
Tank capacity (L)