

XC 30 L

(Ref. 20405030)

Suction of water, dust, and wood dust
Usage intensif spécifique

Norm: EN 60335-2-69, Classe L
Guarantee: 3 ans

Photo et textes non contractuels

Product Information:

"No-bag water and fine or clogging fine dust suction
Automatic unclogging system, the filter is automatically unclogged throug h air pulses, during a 2.2 s cycle every 15 s, without any suction interrupti on
Unpluggable unclogging system
Fitted with an electrical socket to perform a synchronised start using an el ectroportable tool 100 to 2400 W
Main PTFE filter: low dust adhesion, rot-proof and washable
Pre-fitted with adaptors for storage box support, Sortimo or Systainer (opti onal)
Accessory support
Power cable support
Anti-crushing shielded hose
Easy transport (light and reduced dimensions) with a tank fitted with 2 wh eels + 2 brake-swivelling metal castors
Smooth motor start through electronic speed variator
Motor overheat safety device with automatic switching off
Neoprene power table H05 RR-F 3G 1,5 length 7,5 m
Antistatic"

Technical characteristics:

Height (cm) : 52.50
Width (cm) : 38.00
Length (cm) : 55.00
Net weight (Kg) : 17.60
Repairability index
Power (W)
Power (V) 1-phase 230V
Tank Polypropylene
Tank capacity (l) 19,5
Depression (Kpa)
Flow (l/min)
Sound level (dBA)
Atex Zone 22 No
Accessory diameter (mm)
Unclogging automatic
Class-M approved No
Vacuum cleaner filter Class M PTFE flat
Synchro socket Yes
Cable length (m)
Tank capacity (L)

Standard accessories:
- Bent stainless steel tube 400 mm
- Straight stainless steel tubes3 x 350 mm
- hose Ø 36 mm, length 3 m
- water and dust nozzle 300 mm
- flat nozzle 200 mm
- Class M PTFE flat main filter
- Adaptor for electroportable tool