



## 30 CV DA

(Ref. 20502064)

Drilling and tapping of metals, plastic materials and wood, with coolant

**Usage intensif**

Guarantee:  

Photo et textes non contractuels

### Product Information:

Steel cast iron frame, head and stand  
Steel column  
Spindle fitted on bearings  
24V very low voltage controls  
Emergency Stop through mushroom stay put button  
Locking main switch 4 points  
Semi automatic tapping system + instant return  
Automatic down move - 3 feed rates 0.2/0.1/0.05 mm/rev  
Servo detachable chuck protective shield  
Large table mécanicien, Rack-driven table  
Electronic speed variator  
Digital display of the spindle speed  
LED lighting 24 V

### Supplied with:

- Tap-holder chuck M3 to M16
- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift

### Technical characteristics:

Height (cm) : 193.00  
Width (cm) : 56.00  
Length (cm) : 89.00  
Net weight (Kg) : 243.50  
Power(kW)  
Power (V) 3-phase 400V  
Spindle speed (rpm)  
Max. drilling capacity (mm)  
Max. tapping capacity (mm)  
Morse taper MT3  
Column dia (mm)  
Spindle stroke (mm)  
Number of gears  
d: spindle/column distance (mm)  
e: spindle/base distance (mm) 1 180  
f: spindle/table distance (mm)  
Table dimension (mm)  
Distance between table grooves (mm)  
Lighting Yes  
Servo screen Yes  
Reversible vice table No  
Coolant Yes  
Automatic down motion (mm/tr)  
Slow down motion Yes  
Semi automatic tapping Yes  
Cross motion table No