



PRO 22 PEV

(Ref. 20502083)

Dry drilling of metals, plastic materials and wood (optional lubrication)

Usage intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

Steel cast iron frame, head and stand
Steel column
Transmission through Poly V belts with tension adjustment
Spindle fitted on bearings
Adjustable spindle rack motion through return spring
Drilling-depth stop
Electronic speed variator
Digital display of the spindle speed
Emergency Stop through mushroom stay put button
Safety microswitch of the pulley cover
Spindle speed override button
Servo detachable chuck protective shield
LED lighting 3.6 V - 3 W
Tilting table up to 45° with a vernier and a coolant collector + 12-mm table grooves
Rack-driven table

Supplied with:

- Key-less chuck 16 mm
- Chuck shank
- Taper drift
- Vice BSF 120 and clamp set

Technical characteristics:

Height (cm) : 108.50
Width (cm) : 63.50
Length (cm) : 37.00
Net weight (Kg) : 94.07
Power(kW)
Power (V) 1-phase 230V
Spindle speed (rpm)
Max. drilling capacity (mm)
Morse taper MT2
Column dia (mm)
Spindle stroke (mm)
Number of gears
d: spindle/column distance (mm)
e: spindle/base distance (mm)
f: spindle/table distance (mm)
Table dimension (mm)
Lighting Yes
Servo screen Yes
Reversible vice table No
Coolant No
Automatic down motion (mm/tr) No
Slow down motion No
Semi automatic tapping No
Cross motion table No