



SR 450 BSA

(Ref. 20114040)

Dry steel sawing with coolant
Usage très intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

Fully-hydraulic semi automatic cycle of band, arch and arch
Very highly rigid steel cast iron arch
3-point lubrication system through electropump
Detachable vice support
Band tension microswitch through rotation detection
Adjustable band tension through automatic stop safety system in case the band breaks or slips
Adjustable band guides fitted with carbide tips and bearings
Easy rotation of arch with bearings (45° to the right and 60° to the left)
Feed and cutting pressure adjustment system
24V very low voltage controls
Motor protection through thermal circuit breaker
Electrical protection IP54
Locking main switch
Emergency Stop through mushroom stop button
Band cover fitted with a positive microswitch
Hydraulic vice
Bac liquide de refroidissement de 40 litres de contenance
Hot weather adaptation on request
Can be modified to 230V three-phase on request

Technical characteristics:

Height (cm) : 155.00
Width (cm) : 187.00
Length (cm) : 108.00
Net weight (Kg) : 1.00
Power(kW) 1.4 / 2.4
Power (V) 3-phase 400V
Speed (m/min) 32 / 64
Round cutting capacity (mm) at 90° 330
Square cutting capacity (mm) at 90° 320
Rectangle cutting capacity (mm) at 90° 450 x 240
Left round cutting capacity (mm) at 45° 280
Left square cutting capacity (mm) at 45° 250

Supplied with stand, band and cutting stop 600 mm