



Photo et textes non contractuels

SR 264 DG DA

(Ref. 20114122)

Usage intensif

Guarantee:  

Product Information:

Left and right cutting
Autonomous down move of the arch
Very highly rigid steel cast iron arch
Band guides fitted with bearings and carbide tips ensuring a good wear resistance to band
Adjustable front mobile band guide
2-point lubrication system through electropump
Vice support tilting with the arch
Hydraulic vice
24V very low voltage controls
Emergency Stop through mushroom stay put button
Band cover fitted with a microswitch
Motor protection through thermal circuit breaker
Electrical protection IP54
Coaxial reducer motor

Supplie with:

- base
- band saw
- adjustable cut stop

Technical characteristics:

Height (cm) : 140.00
Width (cm) : 66.00
Length (cm) : 140.00
Net weight (Kg) : 295.00
Power(kW) 0.9 / 1.4
Power (V) 3-phases 400V
Speed (m/min) 40 / 80
Round cutting capacity (mm) at 90° 235
Square cutting capacity (mm) at 90° 230
Rectangle cutting capacity (mm) at 90° 280 x 180
Left round cutting capacity (mm) at 45° 185
Left square cutting capacity (mm) at 45° 160
Left rectangle cutting capacity (mm) at 45° 185 x 100
Left round cutting capacity (mm) at 60° 115
Left square cutting capacity (mm) at 60° 80
Left rectangle cutting capacity (mm) at 60° 115 x 80
Vice opening (mm) 300
Working height (mm) 900
Tape (mm) 2710 x 27 x 0.9
Right rectangle cutting capacity (mm) at 45° 185 x 80
Right round cutting capacity (mm) at 45° 165
Left square cutting capacity (mm) at 45° 145