



Photo et textes non contractuels

## SR 350 DG SAV

(Ref. 20114129)

Dry steel, stainless steel and aluminium sawing with coolant with coolant

**Usage intensif**

Guarantee:  

### Product Information:

Fully-hydraulic semi automatic cycle of band, arch and arch  
Electronic speed variator  
Semi automatic down move of the arch  
Very highly rigid steel cast iron arch  
Band guides fitted with bearings and carbide tips ensuring a good wear resistance to band  
Adjustable front mobile band guide  
2-point lubrication system through electropump  
Vice support tilting with the arch  
Hydraulic vice  
24V very low voltage controls  
Emergency Stop through mushroom stay put button  
Band cover fitted with a microswitch  
Motor protection through thermal circuit breaker  
Electrical protection IP54  
Coaxial reducer motor

### Supplied with:

- base
- saw blade
- adjustable cut stop

### Technical characteristics:

Height (cm) : 166.00  
Width (cm) : 75.00  
Length (cm) : 195.00  
Net weight (Kg) : 460.00  
Power(kW) 1,5  
Power (V) 3-phase 400V  
Speed (m/min) 20 : 85  
Round cutting capacity (mm) at 90° 270  
Square cutting capacity (mm) at 90° 260  
Rectangle cutting capacity (mm) at 90° 220 x 350  
Left round cutting capacity (mm) at 45° 240  
Left square cutting capacity (mm) at 45° 220  
Left rectangle cutting capacity (mm) at 45° 170 x 230  
Left round cutting capacity (mm) at 60° 160  
Left square cutting capacity (mm) at 60° 150  
Left rectangle cutting capacity (mm) at 60° 150 x 100  
Vice opening (mm) 375  
Working height (mm) 885  
Tape (mm) 3160 x 27 x 0.9  
Right rectangle cutting capacity (mm) at 45° 140 x 200  
Right round cutting capacity (mm) at 45° 210  
Left square cutting capacity (mm) at 45° 180