



STAR 20 PE

(Ref. 20501018)

Dry drilling of metals, plastic materials and wood
(lubrification en option)

Usage d'appoint

Guarantee:  

Photo et textes non contractuels

Product Information:

Steel cast iron column
V-belt transmission
Spindle fitted on bearings
ON/OFF switch fitted with a lack of voltage coil
Emergency Stop through mushroom stay put button
Safety-grip microswitch around belt cover
Protective shield of servo chuck
Tilting table up to 45 °
Rack-driven table

Supplied with:

- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift
- Screw vice and set of clamps

Technical characteristics:

Height (cm) : 105.50
Width (cm) : 37.00
Length (cm) : 55.00
Net weight (Kg) : 45.50
Power(kW) 0.6
Power (V) 1-phase 230V
Spindle speed (rpm) 180 - 2740
Max. drilling capacity (mm) 20
Morse taper MT2
Column dia (mm) 72
Spindle stroke (mm) 80
Number of gears 12
d: spindle/column distance (mm) 170
e: spindle/base distance (mm) 710
f: spindle/table distance (mm) 505
Table dimension (mm) 250 x 250
Lighting No
Servo screen Yes
Reversible vice table No
Coolant No
Automatic down motion (mm/tr) No
Slow down motion No
Semi automatic tapping No
Cross motion table No