



## STAR 20 PC

(Ref. 20501019)

Dry drilling of metals, plastic materials and wood  
(lubrification en option)

**Usage d'appoint**

Guarantee:  

Photo et textes non contractuels

### Product Information:

Steel cast iron column  
V-belt transmission  
Spindle fitted on bearings  
ON/OFF switch fitted with a lack of voltage coil  
Emergency Stop through mushroom stay put button  
Safety-grip microswitch around belt cover  
Protective shield of servo chuck  
Tilting table up to 45 °  
Rack-driven table

### Supplied with:

- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift
- Screw vice and set of clamps

### Technical characteristics:

Height (cm) : 160.00  
Width (cm) : 34.00  
Length (cm) : 65.00  
Net weight (Kg) : 60.00  
Power(kW) 0.6  
Power (V) 1-phase 230V  
Spindle speed (rpm) 180 - 2740  
Max. drilling capacity (mm) 20  
Morse taper MT2  
Column dia (mm) 72  
Spindle stroke (mm) 80  
Number of gears 12  
d: spindle/column distance (mm) 195  
e: spindle/base distance (mm) 1220  
f: spindle/table distance (mm) 740  
Table dimension (mm) 300 x 310  
Lighting No  
Servo screen Yes  
Reversible vice table No  
Coolant No  
Automatic down motion (mm/tr) No  
Slow down motion No  
Semi automatic tapping No  
Cross motion table No