



STAR 26 PC

(Ref. 20501020)

Dry drilling of metals, plastic materials and wood
(lubrification en option)

Usage d'appoint

Guarantee:  

Photo et textes non contractuels

Product Information:

Steel cast iron column
V-belt transmission
Spindle fitted on bearings
ON/OFF switch fitted with a lack of voltage coil
Emergency Stop through mushroom stay put button
Safety-grip microswitch around belt cover
Protective shield of servo chuck
Tilting table up to 45 °
Rack-driven table

Supplied with:

- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift
- Screw vice and set of clamps

Technical characteristics:

Height (cm) : 162.00
Width (cm) : 40.00
Length (cm) : 76.00
Net weight (Kg) : 82.00
Power(kW) 0.85
Power (V) 1-phase 230V
Spindle speed (rpm) 160 - 3000
Max. drilling capacity (mm) 26
Morse taper MT3
Column dia (mm) 80
Spindle stroke (mm) 85
Number of gears 16
d: spindle/column distance (mm) 210
e: spindle/base distance (mm) 1210
f: spindle/table distance (mm) 710
Table dimension (mm) 355 x 355
Distance between table grooves (mm) 140
Lighting No
Servo screen Yes
Reversible vice table No
Coolant No
Jaw width (mm) 120
Jaw height (mm) 20
Automatic down motion (mm/tr) No
Slow down motion No
Semi automatic tapping No
Cross motion table No