



40 CV

(Ref. 20502023)

Drilling and tapping of metals, plastic materials and wood,
with coolant

Usage intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

Steel cast iron frame, head and stand
Steel column
Spindle fitted on bearings
High efficiency class IE2 motor
24V very low voltage controls
Emergency Stop through mushroom stay put button
Locking main switch 4 points
Semi automatic tapping system + instant return
Servo detachable chuck protective shield
Large table mécanicien, Rack-driven table
Electronic speed variator
Digital display of the spindle speed
LED lighting 24 V

Supplied with:

- Tap-holder chuck M3 to M16
- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift
- BSH 7 vice and set of clamps

Technical characteristics:

Height (cm) : 193.00
Width (cm) : 56.00
Length (cm) : 89.00
Net weight (Kg) : 320.00
Power(kW) 1.5
Power (V) 3-phase 400V
Spindle speed (rpm) 65 : 2000
Max. drilling capacity (mm) 40
Max. tapping capacity (mm) M20
Morse taper MT4
Column dia (mm) 115
Spindle stroke (mm) 150
Number of gears Variable
d: spindle/column distance (mm) 265
e: spindle/base distance (mm) 1 040
f: spindle/table distance (mm) 140-860
Table dimension (mm) 560 x 475
Distance between table grooves (mm) 220
Lighting Yes
Servo screen Yes
Reversible vice table No
Coolant Yes
Automatic down motion (mm/tr) No
Slow down motion No
Semi automatic tapping Yes
Cross motion table No