



30 CTE IE3

(Ref. 20502063)

Drilling metals, plastic materials and wood, with coolant

Usage intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

Steel cast iron frame, head and stand
Steel column
V-belt transmission with tension adjustment
Spindle fitted on bearings
Adjustable spindle rack motion through return spring
Drilling-depth stop
High-efficiency IE3 motor
Controls
Emergency Stop through mushroom stay put button
Safety microswitch of the pulley cover
Servo polycarbonate screen
LED lighting 24 V
2-position reversible vice table, vernier
Vice fitted on guideways
Rack-driven table

Supplied with:

- Self-clamping chuck 16 mm
- Chuck shank

Technical characteristics:

Height (cm) : 182.00
Width (cm) : 53.00
Length (cm) : 84.00
Net weight (Kg) : 235.00
Power(kW) 1.5
Power (V) 3-phase 400V
Spindle speed (rpm) 230 - 1910
Max. drilling capacity (mm) 30
Morse taper MT3
Column dia (mm) 90
Spindle stroke (mm) 125
Number of gears 9
d: spindle/column distance (mm) 225
e: spindle/base distance (mm) 1 275
f: spindle/table distance (mm) 245 - 765
Table dimension (mm) 350 x 350
Distance between table grooves (mm) 2 x 75
Lighting Yes
Servo screen Yes
Reversible vice table Yes
Coolant Yes
Jaw width (mm) 120
Jaw height (mm) 40
Opening (mm) 120
Automatic down motion (mm/tr) No
Slow down motion No
Semi automatic tapping No
Cross motion table No