



## PC23V

(Ref. 20502074)

Usage régulier

Garantie:  

Photo et textes non contractuels

### Product Information:

Double table, a special for metal and a special for wood Metal table:  
square reclining up to 45°, with cutting liquid scavenger, T grooves  
Wood table: rectangular 600 x 300 mm, steerable and reclining in both directions, support rule with tightening wheels, removable center circle for deep drilling, side stop with tightening wheel, holed table for use of grasshoppers for tightening parts  
Variable speed system by single handle  
Transmission by notched belts and steel pulleys  
Aircast column  
Spindle mounted on ball bearings  
Switch on/off with a coil that lacks voltage  
Stopping punch to hook  
Enslaved chuck protection screen  
Moving the table by rack  
Digital display spindle speed  
LED lighting  
Pulley hood equipped with a claw safety microruptor

### Standard delivered accessories:

- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift
- Screw vice and set of clamps

### Technical characteristics:

Height (cm) : 164.00  
Width (cm) : 60.50  
Length (cm) : 78.00  
Net weight (Kg) : 90.00  
Power(kW) 0,9  
Power (V) 1-phase 230V  
Spindle speed (rpm) 460 : 2200  
Max. drilling capacity (mm) 23  
Morse taper MT2  
Column dia (mm) 72  
Spindle stroke (mm) 115  
Number of gears Variable  
d: spindle/column distance (mm) 190  
e: spindle/base distance (mm) 1150  
f: spindle/table distance (mm) 650  
Table dimension (mm) 305x305 / 600x300  
Lighting Oui  
Servo screen Oui  
Reversible vice table No  
Coolant No  
Automatic down motion (mm/tr) Non  
Slow down motion Non  
Semi automatic tapping No  
Cross motion table No