



SPC 40 TE DL

(Ref. 20601124)

Drilling metals, plastic materials and wood, with coolant

Usage très intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

Slow down motion
Steel cast iron frame, head and stand
Steel column
Machined aluminium pulleys
Transmission through V belts with rapid adjustment of tension
Spindle fitted on bearings
Adjustable spindle rack motion through return spring
2-gear motor
24V very low voltage controls
ON/OFF
Switching on lamp
Emergency Stop through mushroom stop button
3-point locking circuit breaker

Detachable servo protective shield
24V lighting
Electrical protection IP54
Noise level 50 dB
3-position reversible vice table (with vernier), V jaws to drill tubes
Vice fitted on guideways to center the part to drill
Rack-driven table, graisseur de la vis sans fin
Hot weather adaptation on request
Can be modified to 230V three-phase on request

Supplied with:

- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift

Technical characteristics:

Height (cm) : 185.00
Width (cm) : 47.50
Length (cm) : 90.00
Net weight (Kg) : 365.00
Power(kW) 0.8 / 1.47
Power (V) 3-phase 400V
Spindle speed (rpm) 45 - 1650
Max. drilling capacity (mm) 40
Morse taper MT4
Column dia (mm) 120
Spindle stroke (mm) 150
Number of gears 14
d: spindle/column distance (mm) 300
e: spindle/base distance (mm) 1 150
f: spindle/table distance (mm) 50-610
Table dimension (mm) 420 x 420
Distance between table grooves (mm) 150
Lighting Yes
Servo screen Yes
Reversible vice table Yes
Coolant Yes
Jaw width (mm) 130
Jaw height (mm) 40
Opening (mm) 150
Automatic down motion (mm/tr) No
Slow down motion Yes
Semi automatic tapping No
Cross motion table No