



## SPC 32 TE

(Ref. 20601126)

Drilling metals, plastic materials and wood, with coolant

**Usage très intensif**

Guarantee:  

Photo et textes non contractuels

### Product Information:

Steel cast iron frame, head and stand  
Steel column  
Machined aluminium pulleys  
Transmission through V belts with rapid adjustment of tension  
Spindle fitted on bearings  
Adjustable spindle rack motion through return spring  
2-gear motor  
24V very low voltage controls  
ON/OFF  
Switching on lamp  
Emergency Stop through mushroom stop button  
3-point locking circuit breaker  
Detachable servo protective shield  
24V lighting  
Electrical protection IP54  
Noise level 50 dB  
3-position reversible vice table (with vernier), V jaws to drill tubes  
Vice fitted on guideways to center the part to drill  
Rack-driven table, graisseur de la vis sans fin  
Hot weather adaptation on request  
Can be modified to 230V three-phase on request

### Supplied with:

- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift

### Technical characteristics:

Height (cm) : 180.00  
Width (cm) : 43.50  
Length (cm) : 88.00  
Net weight (Kg) : 290.00  
Power(kW) 0.6/1.1  
Power (V) 3-phase 400V  
Spindle speed (rpm) 35-1980  
Max. drilling capacity (mm) 32  
Morse taper MT3  
Column dia (mm) 110  
Spindle stroke (mm) 110  
Number of gears 14  
d: spindle/column distance (mm) 280  
e: spindle/base distance (mm) 1 210  
f: spindle/table distance (mm) 50-630  
Table dimension (mm) 350 x 350  
Distance between table grooves (mm) 130  
Lighting Yes  
Servo screen Yes  
Reversible vice table Yes  
Coolant Yes  
Jaw width (mm) 100  
Jaw height (mm) 30  
Opening (mm) 100  
Automatic down motion (mm/tr) No  
Slow down motion No  
Semi automatic tapping No  
Cross motion table No