



## SPC 40 TC DL

(Ref. 20601138)

Drilling metals, plastic materials and wood, with coolant

**Usage très intensif**

Guarantee:  

Photo et textes non contractuels

### Product Information:

Cross move table, Slow down motion  
Steel cast iron frame, head and stand  
Steel column  
Machined aluminium pulleys  
Transmission through V belts with rapid adjustment of tension  
Spindle fitted on bearings  
Adjustable spindle rack motion through return spring  
2-gear motor  
24V very low voltage controls :  
- ON/OFF  
- Switching on lamp  
- Emergency Stop through mushroom stop button  
- 3-point locking circuit breaker  
Detachable servo protective shield  
24V lighting  
Electrical protection IP54  
Noise level 50 dB  
Rack-driven table, greasor de la vis sans fin  
Hot weather adaptation on request  
Can be modified to 230V three-phase on request  
Machined aluminium pulleys

**Supplied with Self-clamping chuck and Chuck shank**

### Technical characteristics:

Height (cm) : 185.00  
Width (cm) : 47.50  
Length (cm) : 90.00  
Net weight (Kg) : 570.00  
Power(kW) 0.8 / 1.47  
Power (V) 3-phase 400V  
Spindle speed (rpm) 45-1650  
Max. drilling capacity (mm) 40  
Milling capacity (mm) 80  
Morse taper MT4  
Column dia (mm) 140  
Spindle stroke (mm) 150  
Number of gears 14  
d: spindle/column distance (mm) 300  
e: spindle/base distance (mm) 1 150  
f: spindle/table distance (mm) 50-610  
Table dimension (mm) 300 x 540  
Distance between table grooves (mm) 150  
Lighting Yes  
Servo screen Yes  
Reversible vice table No  
Coolant Yes  
Transversal / longitudinal stroke (mm) 300 x 410  
Automatic down motion (mm/tr) No  
Slow down motion Yes  
Semi automatic tapping No  
Cross motion table Yes