



## SPC 40 TC DA DL

(Ref. 20601141)

Drilling metals, plastic materials and wood, with coolant

**Usage très intensif**

Guarantee:  

Photo et textes non contractuels

### Product Information:

Cross move table, Slow down motion, automatic down motion (3 feed rates)

Steel cast iron frame, head and stand

Steel column

Machined aluminium pulleys

Transmission through V belts with rapid adjustment of tension

Spindle fitted on bearings

Adjustable spindle rack motion through return spring

2-gear motor

24V very low voltage controls :

- ON/OFF

- Switching on lamp

- Emergency Stop through mushroom stop button

- 3-point locking circuit breaker

Detachable servo protective shield

24V lighting

Electrical protection IP54

Noise level 50 dB

Rack-driven table, graisseur de la vis sans fin

Hot weather adaptation on request

Can be modified to 230V three-phase on request

Machined aluminium pulleys

### Technical characteristics:

Height (cm) : 185.00

Width (cm) : 47.50

Length (cm) : 90.00

Net weight (Kg) : 600.00

Power(kW) 2.2

Power (V) 3-phase 400V

Spindle speed (rpm) 45-1650

Max. drilling capacity (mm) 40

Milling capacity (mm) 80

Morse taper MT4

Column dia (mm) 140

Spindle stroke (mm) 150

Number of gears 14

d: spindle/column distance (mm) 300

e: spindle/base distance (mm) 1 150

f: spindle/table distance (mm) 50-610

Table dimension (mm) 300 x 540

Distance between table grooves (mm) 150

Lighting Yes

Servo screen Yes

Reversible vice table No

Coolant Yes

Transversal / longitudinal stroke (mm) 300 x 410

Automatic down motion (mm/tr) 0.06 - 0.12 - 0.25

Slow down motion Yes

Semi automatic tapping No

Cross motion table Yes

**Supplied with Self-clamping chuck and Chuck shank**