



## PRO 22 PEV

(Ref. 20502083)

Dry drilling of metals, plastic materials and wood  
(lubrification en option)

**Usage intensif**

Guarantee:  

Photo et textes non contractuels

### Product Information:

Steel cast iron frame, head and stand  
Steel column  
Transmission through Poly V belts with tension adjustment  
Spindle fitted on bearings  
Adjustable spindle mack motion through return spring  
Drilling-depth stop  
Electronic speed variator  
Digital display of the spindle speed  
Emergency Stop through mushroom stay put button  
Safety microswitch of the pulley cover  
Spindle speed override buTon  
Servo detachable chuck protective shield  
LED lighting 3.6 V - 3 W  
Tilting table up to 45° with a vernier and a coolant collector + 12-  
mm table grooves  
Rack-driven table

#### Supplied with:

- Key-less chuck 16 mm
- Chuck shank
- Taper drift
- Vice BSF 120 and clamp set

### Technical characteristics:

Height (cm) : 108.50  
Width (cm) : 63.50  
Length (cm) : 37.00  
Net weight (Kg) : 87.08  
Power(kW) 1.2  
Power (V) 1-phase 230V  
Spindle speed (rpm) 150 : 5000  
Max. drilling capacity (mm) 22  
Morse taper MT2  
Column dia (mm) 80  
Spindle stroke (mm) 90  
Number of gears Variable  
d: spindle/column distance (mm) 180  
e: spindle/base distance (mm) 650  
f: spindle/table distance (mm) 140 - 425  
Table dimension (mm) 280 x 280  
Lighting Yes  
Servo screen Yes  
Reversible vice table No  
Coolant No  
Automatic down motion (mm/tr) No  
Slow down motion No  
Semi automatic tapping No  
Cross motion table No