



Photo et textes non contractuels

EXPERT 23 PCVB

(Ref. 20502107)

Dry drilling of metals, plastics and wood (optional cooling system)

Usage régulier

Guarantee:  

Product Information:

Double table, a special for metal and a special for wood Metal table: square reclining up to 45°, with cutting liquid scavenger, T grooves Wood table: rectangular 600 x 300 mm, steerable and reclining in both directions, support rule with tightening wheels, removable center circle for deep drilling, side stop with tightening wheel, hinged table for use of grasshoppers for tightening parts Variable speed system by single handle Transmission by notched belts and steel pulleys Aircast column Spindle mounted on ball bearings Switch on/off with a coil that lacks voltage Stopping punch to hook Enslaved chuck protection screen Moving the table by rack Digital display spindle speed LED lighting Pulley hood equipped with a claw safety microswitch

Standard delivered accessories:

- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift
- Screw vice and set of clamps

Technical characteristics:

Height (cm) : 164.00
Width (cm) : 60.50
Length (cm) : 78.00
Net weight (Kg) : 90.42
Power(kW) 0,9
Power (V) 1-phase 230V
Spindle speed (rpm) 460 : 2200
Max. drilling capacity (mm) 23
Morse taper MT2
Column dia (mm) 72
Spindle stroke (mm) 115
Number of gears Variable
d: spindle/column distance (mm) 190
e: spindle/base distance (mm) 1150
f: spindle/table distance (mm) 650
Table dimension (mm) 305x305 / 600x300
Lighting Oui
Servo screen Oui
Reversible vice table No
Coolant No
Automatic down motion (mm/tr) Non
Slow down motion Non
Semi automatic tapping No
Cross motion table No