



SPC 32 TC VEL DL

(Ref. 20601131)

Drilling metals, plastic materials and wood, with coolant
Usage très intensif

Guarantee:  **3** 

Photo et textes non contractuels

Product Information:

Cross move table,
 Slow down motion
 Electronic speed variator
 Steel cast iron frame, head and stand
 Steel column
 Machined aluminium pulleys
 Transmission through V belts with rapid adujstment of tension
 Spindle fitted on bearings
 Adjustable spindle mack motion through return spring
 24V very low voltage controls :
 - ON/OFF
 - Switching on lamp
 - Emergency Stop through mushroom stay put button
 - 3-point locking circuit breaker
 Detachable servo protective shield
 24V lighting
 Electrical protection IP54
 Noise level 50 dB
 Rack-driven table, graisseur de la vis sans fin
 Hot weather adaptation on request

Technical characteristics:

Height (cm) : 180.00
 Width (cm) : 43.50
 Length (cm) : 88.00
 Net weight (Kg) : 350.00
 Power(kW) 1.5
 Power (V) 3-phase 400V
 Spindle speed (rpm) 80 - 2030
 Max. drilling capacity (mm) 32
 Milling capacity (mm) 60
 Morse taper MT3
 Column dia (mm) 110
 Spindle stroke (mm) 110
 Number of gears 14
 d: spindle/column distance (mm) 280
 e: spindle/base distance (mm) 1 210
 f: spindle/table distance (mm) 50-630
 Table dimension (mm) 240 x 600
 Distance between table grooves (mm) 130
 Lighting Yes
 Servo screen Yes

Can be modified to 230V three-phase on request
Machined aluminium pulleys

Transversal / longitudinal stroke (mm) 265 x 480
Automatic down motion (mm/tr) No
Slow down motion Yes
Semi automatic tapping No
Cross motion table Yes

Supplied with Self-clamping chuck and Chuck shank