



343 S

(Ref. 20105051)

Sanding of metals, wood, plastics
Usage très intensif

Guarantee:  **3** 

Photo et textes non contractuels

Product Information:

- Self-adhesive abrasive disk Ø 350 mm
- Tilting table on stone-polisher side from 0° to 45°
- Transmission through anti-slipping rubber roller
- Graphite-coated canvas ensuring a good running of the band
- Lack of tension-coil switch
- Thermal circuit breaker
- 2-gear motor
- Emergency Stop through mushroom stay put button
- 24V very low voltage control
- Reinforced metal sheet protective cover fitted with dust collection nozzle Ø 100 mm
- R0° to 90° orientable band cover for horizontal or vertical job, and band end job
- Hot weather adaptation on request
- Can be modified to 230V three-phase on request
- Supplied fitted on stand
- Optional suction system (20105053)

Technical characteristics:

- Height (cm) : 123.00
- Width (cm) : 66.00
- Length (cm) : 70.00
- Net weight (Kg) : 100.00
- Power(kW) 1.27 / 1.7
- Power (V) 3-phase 400V
- Rotation speed (rpm) 1400 / 2800
- Endless band dimension (mm) 1500 x 120
- Working surface table (mm) 445 x 120
- Band speed (m/s) 15 / 30
- Integrated dust suction optional

Supplied with:

- a brown corundum GR60 endless band
- a self-adhesive brown corundum GR60 abrasive disk dia 350mm