



363 S

(Ref. 20105052)

Sanding of metals, wood, plastics

Usage très intensif

Guarantee:  **3** 

Photo et textes non contractuels

Product Information:

brush made of brassed steel wires \varnothing 250 mm, thickness 35 mm, bore hole 32 mm
Transmission through anti-slipping rubber roller
Graphite-coated canvas ensuring a good running of the band
Lack of tension-coil switch
Thermal circuit breaker
2-gear motor
Emergency Stop through mushroom stay put button

24V very low voltage control
Reinforced metal sheet protective cover fitted with dust collection nozzle \varnothing 100 mm
R0 \varnothing to 90 \varnothing orientable band cover for horizontal or vertical job, and band end job
Hot weather adaptation on request
Can be modified to 230V three-phase on request
Supplied fitted on stand
Optional suction system (20105053)

Supplied with his Stand

Technical characteristics:

Height (cm) : 122.00
Width (cm) : 70.00
Length (cm) : 83.00
Net weight (Kg) : 100.00
Power(kW) 1.27 / 1.7
Power (V) 3-phase 400V
Rotation speed (rpm) 1400 / 2800
Endless band dimension (mm) 1500 x 120
Working surface table (mm) 445 x 120
Band speed (m/s) 15 / 30
Integrated dust suction optional