



121

(Ref. 20113010)

Dry grinding and polishing of ferrous metals
Usage très intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

- "Cast aluminium body
- Fitted with self-lubricated oiltight bearings
- Control box complying with high school and administration requirements
- 4-point locking Start/Stop switch
- Lack of voltage-coil safety device
- Emergency Stop with mushroom stay put button
- Polycarbonate protective shield
- Motor internal automatic heat protection
- Pressed metal sheet carters fitted with a nozzle to collect dust

- Adjustable anti-spark shield and tool-holders 2 mm away from the wheel
- Hot weather adaptation on request
- 3-phase 230V version of the bench grinder on request

Supplied with:

- Grinding Wheel A 60 M
- Brass Wire Brush

Technical characteristics:

- Height (cm) : 37.00
- Width (cm) : 24.00
- Length (cm) : 53.00
- Net weight (Kg) : 15.80
- Power(kW) 0.55
- Power (V) 3-phase 400V
- Rotation speed 1 (rpm) 2 800
- Wheel-1 dimension (mm) 150 x 20 x 16
- Brush dimensions (mm) 150 x 20 x 16
- Wheel-1 grain A 60 M
- Brush wire nature Brass coated steel
- Diameter (mm)