



ULTRA 150 TMT FR

(Ref. 20113134)

Dry grinding of ferrous metals
Usage très intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

- Cast aluminium body
- Fitted with self-lubricated oiltight bearings
- Electrical brake powered by an Emergency Stop, stop in less than 5 seconds
- Control box complying with high school and administration requirements
- 24V very low voltage controls
- Start/Stop switch
- Switching on lamp
- 3-point locking circuit breaker
- Lack of voltage-coil safety device
- Polycarbonate protective shield
- Motor internal automatic heat protection
- Pressed metal sheet carters fitted with a nozzle to collect dust
- Adjustable anti-spark shield and tool-holders 2 mm away from the wheel
- Hot weather adaptation on request
- 3-phase 230V version of the bench grinder on request

Supplied with:

- Grinding Wheel A 24 R
- Grinding Wheel A 60 M

Technical characteristics:

- Height (cm) : 0.00
- Width (cm) : 0.00
- Length (cm) : 0.00
- Net weight (Kg) : 0.00
- Power(kW) 0.55
- Power (V) 3-phase 400V
- Rotation speed 1 (rpm) 2800
- Wheel-1 dimension (mm) 150 x 20 x 16
- Wheel-2 dimension (mm) 150 x 20 x 16
- Wheel-1 grain A 24 R
- Wheel-2 grain A 60 M
- Diameter (mm) 150