




ULTRA 200 TMBT

(Ref. 20113137)

Dry grinding and band polishing of ferrous metals
Usage très intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

Cast aluminium body
Fitted with self-lubricated oiltight bearings
Control box complying with high school and administration requirements
4-point locking Start/Stop switch
Lack of voltage-coil safety device
Emergency Stop with mushroom stay put button
Polycarbonate protective shield
Motor internal automatic heat protection
Pressed metal sheet carters fitted with a nozzle to collect dust - diameter 30 mm
Pressed metal sheet band carters fitted with a nozzle to collect dust - diameter 100 mm
0° to 90° orientable band carter to work horizontally or vertically
Adjustable anti-spark shield and tool-holders 2 mm away from the wheel
Hot weather adaptation on request
3-phase 230V version of the bench grinder on request

Technical characteristics:

Height (cm) : 63.00
Width (cm) : 27.00
Length (cm) : 62.00
Net weight (Kg) : 37.00
Power(kW)
Power (V) 3-phase 400V
Rotation speed 1 (rpm)
Endless band dimension (mm)
Wheel-1 dimension (mm)
Wheel-1 grain
Band grain
Diameter (mm)

Supplied with:

- Grinding Wheel A 60 M
- Belt GR80