



## SR 450 BSA

(Ref. 20114040)

Dry steel sawing with coolant

**Usage très intensif**

Guarantee:  **3** 

**Photo et textes non contractuels**

### Product Information:

Fully-hydraulic semi automatic cycle of band, arch and arch  
Very highly rigid steel cast iron arch  
3-point lubrication system through electropump  
Detachable vice support  
Band tension microswitch through rotation detection  
Adjustable band tension through automatic stop safety system in case the band breaks or slips  
Adjustable band guides fitted with carbide tips and bearings  
Easy rotation of arch with bearings (45° to the right and 60° to the left)  
Feed and cutting pressure adjustment system  
24V very low voltage controls  
Motor protection through thermal circuit breaker  
Electrical protection IP54  
Locking main switch  
Emergency Stop through mushroom stay put button  
Band cover fitted with a positive microswitch  
Hydraulic vice  
Bac liquide de refroidissement de 40 litres de contenance  
Hot weather adaptation on request  
Can be modified to 230V three-phase on request

### Technical characteristics:

Height (cm) : 168.00  
Width (cm) : 170.00  
Length (cm) : 190.00  
Net weight (Kg) :  
Power(kW) 1.4 / 2.4  
Power (V) 3-phase 400V  
Speed (m/min) 32 / 64  
Round cutting capacity (mm) at 90° 330  
Square cutting capacity (mm) at 90° 320  
Rectangle cutting capacity (mm) at 90° 450 x 240  
Left round cutting capacity (mm) at 45° 280  
Left square cutting capacity (mm) at 45° 250

**Supplied with stand, band and cutting stop 600 mm**