



SR 320 BSA VA

(Ref. 20114114)

Usage très intensif

Guarantee:  **3** 

Photo et textes non contractuels

Product Information:

Fully-hydraulic semi automatic cycle of band, arch and arch Digital reading and adjustment of:

- Variable speed of the band
- Up move of the arch
- Number of cuts made

Very highly rigid cast aluminium arch 3-point lubrication system through electric pump Detachable vice support Band tension microswitch through rotation detection Adjustable band tension through automatic stop safety system in case the band breaks or slips Adjustable band guides fitted with carbide tips and bearings Easy rotation of arch with bearings (45° to the right and 60° to the left) Feed and cutting pressure adjustment system 24V very low voltage controls Motor protection through thermal circuit breaker Electrical protection IP54 Locking main switch Emergency Stop through mushroom stay put button Band cover fitted with a positive microswitch Hydraulic vice Tank of cooling fluid (capacity 40 litres) Hot weather adaptation on request Three-phase 230 V modification on request

Technical characteristics:

Height (cm) : 132.00
Width (cm) : 150.00
Length (cm) : 96.00
Net weight (Kg) : 620.00
Power(kW) 2.2
Power (V) 3-phase 400V
Speed (m/min) 20 : 100
Round cutting capacity (mm) at 90° 275
Square cutting capacity (mm) at 90° 265
Rectangle cutting capacity (mm) at 90° 320 x 230
Left round cutting capacity (mm) at 45° 200
Left square cutting capacity (mm) at 45° 185
Left rectangle cutting capacity (mm) at 45° 185 x 220
Left round cutting capacity (mm) at 60° 130
Left square cutting capacity (mm) at 60° 130
Left rectangle cutting capacity (mm) at 60° 120 x 120
Vice opening (mm) 320

Supplied with stand, band and cutting stop 600 mm