



SR 374 DG SAV

(Ref. 20114117)

Dry steel, stainless steel and aluminium sawing with coolant with coolant

Usage intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

"Fully-hydraulic semi automatic cycle of band, arch and arch
Electronic speed variator
Semi automatic down move of the arch
Very highly rigid steel cast iron arch
Band guides fitted with bearings and carbide tips ensuring a good wear resistance to band
Adjustable front mobile band guide
2-point lubrication system through electropump
Vice support tilting with the arch
Hydraulic vice
24V very low voltage controls
Emergency Stop through mushroom stay put button
Band cover fitted with a microswitch
Motor protection through thermal circuit breaker
Electrical protection IP54
Coaxial reducer motor

Technical characteristics:

Height (cm) : 200.00
Width (cm) : 230.00
Length (cm) : 155.00
Net weight (Kg) : 665.00
Power(kW) 2.2
Power (V) 3-phase 400V
Speed (m/min) 15 : 90
Round cutting capacity (mm) at 90° 300
Square cutting capacity (mm) at 90° 290
Rectangle cutting capacity (mm) at 90° 370 x 185
Left round cutting capacity (mm) at 45° 240
Left square cutting capacity (mm) at 45° 220
Left rectangle cutting capacity (mm) at 45° 240 x 100
Left round cutting capacity (mm) at 60° 150
Left square cutting capacity (mm) at 60° 145
Left rectangle cutting capacity (mm) at 60° 150 x 100
Vice opening (mm) 375
Working height (mm) 915
Tape (mm) 3150 x 27 x 0.9
Right rectangle cutting capacity (mm) at 45° 240 x 100
Right round cutting capacity (mm) at 45° 220
Left square cutting capacity (mm) at 45° 190