



Photo et textes non contractuels

Product Information:

Left and right cutting
Autonomous down move of the arch
Electronic variable speed
Very highly rigid steel cast iron arch
Band guides fitted with bearings and carbide tips ensuring a good wear resistance to band
Adjustable front mobile band guide
2-point lubrication system through electropump
Vice support tilting with the arch
Hydraulic vice
24V very low voltage controls
Emergency Stop through mushroom stay put button
Band cover fitted with a microswitch
Motor protection through thermal circuit breaker
Electrical protection IP54
Coaxial reducer motor

Supplie with:

- base
- band saw
- adjustable cut stop

SR 264 DG DAV

(Ref. 20114121)

Usage intensif

Guarantee: CE

Technical characteristics:

Height (cm) : 140.00
Width (cm) : 66.00
Length (cm) : 140.00
Net weight (Kg) : 312.00
Power(kW) 1,4
Power (V) 3-phases 400V
Speed (m/min) 15 : 90
Round cutting capacity (mm) at 90°
Squre cutting capacity (mm) at 90°
Rectangle cutting capacity (mm) at 90°
Left round cutting capacity (mm) at 45°
Left square cutting capacity (mm) at 45°
Left rectangle cutting capacity (mm) at 45°
Left round cutting capacity (mm) at 60°
Left square cutting capacity (mm) at 60°
Left rectangle cutting capacity (mm) at 60°
Vice opening (mm)
Working height (mm)
Tape (mm)
Right rectangle cutting capacity (mm) at 45°
Right round cutting capacity (mm) at 45°
Left square cutting capacity (mm) at 45°