



## SR 211 DAV

(Ref. 20114130)

Dry steel, stainless steel and aluminium sawing with coolant with coolant

**Usage régulier**

Guarantee:  

Photo et textes non contractuels

### Product Information:

- Steel cast iron arch
- Band guides fitted with bearings ensuring an excellent wear-resistance of band saw blade
- Adjustable front mobile band guide
- Gravity-feed separate down move through oil cylinder
- 2-point lubrication system through electropump
- Band-tension microswitch and pressure gauge
- Fast-tightening vice mounted on clearance catch-up slide
- Electronic speed variator
- Front control panel
- 24V very low voltage controls
- Emergency Stop through mushroom stay put button
- Band cover fitted with a positive microswitch
- Motor protection through thermal circuit breaker
- Coaxial reducer motor

### Comes with:

- base
- band saw blade
- 500 mm adjustable cut stop

### Technical characteristics:

- Height (cm) : 160.00
- Width (cm) : 146.00
- Length (cm) : 100.00
- Net weight (Kg) : 155.00
- Power(kW) 1.5
- Power (V) 1-phase 230V
- Speed (m/min) 20 : 90
- Round cutting capacity (mm) at 90° 170
- Square cutting capacity (mm) at 90° 150
- Rectangle cutting capacity (mm) at 90° 190 x 150
- Left round cutting capacity (mm) at 45° 125
- Left square cutting capacity (mm) at 45° 95
- Left rectangle cutting capacity (mm) at 45° 120 x 95
- Vice opening (mm) 200
- Working height (mm) 880
- Tape (mm) 2080 x 20 x 0.9