



Photo et textes non contractuels

Product Information:

Steel cast iron arch
Band guides fitted with bearings and carbide tips ensuring a good wear resistance to band
Adjustable front mobile band guide
Gravity-feed separate down move through oil cylinder
2-point lubrication system through electropump
Band-tension microswitch and pressure gauge
Rapid clamping vice monté sur glissière à rattrapage de jeu
Band speed variator
Front control panel
24V very low voltage controls
Emergency Stop through mushroom stay put button
Band cover fitted with a positive microswitch
Motor protection through thermal circuit breaker
Coaxial reducer motor

EXPERT 250 SR DAV MONO

(Ref. 20114135)

Dry steel, stainless steel and aluminium sawing with coolant
Usage régulier

Guarantee: **3** **CE**

Technical characteristics:

Height (cm) : 173.00
Width (cm) : 54.00
Length (cm) : 180.00
Net weight (Kg) : 212.00
Power(kW)
Power (V) 1-phase 230V
Speed (m/min)
Round cutting capacity (mm) at 90°
Squre cutting capacity (mm) at 90°
Rectangle cutting capacity (mm) at 90°
Left round cutting capacity (mm) at 45°
Left square cutting capacity (mm) at 45°
Left rectangle cutting capacity (mm) at 45°
Left round cutting capacity (mm) at 60°
Left square cutting capacity (mm) at 60°
Left rectangle cutting capacity (mm) at 60°
Vice opening (mm)
Working height (mm)
Tape (mm)

Supplied with base, saw blade and 500 mm adjustable cut stop