



Photo et textes non contractuels

## EXPERT 250 SR DGDV

(Ref. 20114137)

Dry steel, stainless steel and aluminium sawing with coolant with coolant

**Usage régulier**

Guarantee:  

### Product Information:

Cuts left and right  
Aircast fram  
Saw blade guides equipped with bearings and carbide pads to ensure excellent resistance to saw blade wear  
Adjustable anterior tape guide  
Autonomous descent by gravity controlled by hydraulic cylinder  
2-point electro-pump lubrication device  
Safety micro-switch and tension gauge saw blade  
Fast-tightening set mounted on game catch-up slide  
Variable speed saw blade  
Control desk in front  
Very low voltage controls 24 V  
Stopping punch to hook  
Carter saw equipped with a positive micro-reuptor  
Motor protection by heat breaker  
Motor with coaxial gearbox

**Supplied with base, saw blade and 500 mm adjustable cut stop**

### Technical characteristics:

Height (cm) : 180.00  
Width (cm) : 100.00  
Length (cm) : 185.00  
Net weight (Kg) : 306.00  
Power(kW) 1.1  
Power (V) 3-phase 400V  
Speed (m/min) 20 : 85  
Round cutting capacity (mm) at 90° 225  
Squire cutting capacity (mm) at 90° 225  
Rectangle cutting capacity (mm) at 90° 250 x 150  
Left round cutting capacity (mm) at 45° 150  
Left square cutting capacity (mm) at 45° 150  
Left rectangle cutting capacity (mm) at 45° 130 x 190  
Left round cutting capacity (mm) at 60° 90  
Left square cutting capacity (mm) at 60° 90  
Left rectangle cutting capacity (mm) at 60° 95 x 90  
Vice opening (mm) 250  
Working height (mm) 930  
Tape (mm) 2470 x 27 x 0.9  
Right rectangle cutting capacity (mm) at 45° 45 x 160  
Right round cutting capacity (mm) at 45° 140  
Left square cutting capacity (mm) at 45° 115