



Photo et textes non contractuels

PRECICUT 350 PLUS

(Ref. 20116000)

Dry or water electric cutting of tiles et Materials
Usage régulier

Guarantee:  

Product Information:

Machine designed to perform precise cuts of material for buidings structur al works
Mobile-table machine
Fitting diamond disk - diameters 300 or 350 mm
Disk cooling down on both faces
Adjustable-height and tilting head to perform bevelled cuts
Supporting scale with orientable cutting stop
Cooling circuit of the disk with electric pump with an adjustable-cutting-off knob to ensure a better efficiency
Roller-carriage moving on rails separated from the frame
Anti-tilting device of the carriage
Aluminium frame
Folding feet under the frame
Transport wheels of the machine

Technical characteristics:

Height (cm) : 58.50
Width (cm) : 84.00
Length (cm) : 122.00
Net weight (Kg) : 81.00
Power (W) 2200
Power (V) 1-phase 230V
Rotation speed (rpm) 2800
Disk diameter (mm) 300 / 350
Disk bore (mm) 25.4
Length cutting capacity (mm) 90° 630
Height cutting capacity (mm) 90° 100
Left height cutting capacity (mm) 45° 630
Left heighth cutting capacity (mm) 45° 60
Water tank (l) 45
Tile thickness (mm) 20

Standard delivered accessories:

Single-phase female socket (without power cable)
Disk mount key
Disk lock axis
Flat wrench 13 mm
Delivery WITHOUT diamond disc